

28th ANNUAL AEROSOL CONFERENCE

American Association for Aerosol Research, Oct 26 – 30, 2009 Minneapolis, MN

Session 10F: Combustion

The Effect of Diesel Particle Filters and Selective Catalytic Reduction - A Predictive Framework for Ultrafine Particle Formation, Toxicity and Chemical Composition

**Jorn Dinh Herner, Shaohua Hu, William Robertson, Tao Huai,
John Collins, Harry Dwyer, and Alberto Ayala**


California Air Resources Board




California Environmental Protection Agency

Air Resources Board

The statements and opinions expressed in this presentation are solely the authors' and do not represent the official position of the California Air Resources Board. The mention of trade names, products, and organizations does not constitute endorsement or recommendation for use.



Acknowledgements:



CARB Staff: Keshav Sahay, John Karim, Ralph Rodas, George Gatt, Paul Rieger, Oliver Chang, Christine Maddox, Subhasis Biswas, and many more.

USC: Prof. Constantinos Sioutas, Vishal Verma, Harish Phuleria

Co-Sponsors:



In Kind Contributors:




CALIFORNIA DEPARTMENT OF
TRANSPORTATION



Experimental Setup

CARB Heavy duty Diesel Emissions Test Laboratory


- Ultra Low Sulfur Diesel (6ppm)
- CVS - Dilution Tunnel
- Real time particle measurements:
EEPS, DMS500, SMPS, CPC's, DC, PAS
- Cycles:
Cruise at 50mph, UDDSx2, Idle



Test Matrix

4 vehicles, 6 configurations + Baseline

Aftertreatment - (red signifies catalyzed surface)



Vehicles



1998 Cummins Diesel
11L, 360,000 miles



1999 International Diesel
7.6L, 40,000 miles




2003 Cummins Diesel
5.9L, 50,000 miles



2006 Cummins Diesel w/ Allison
Hybrid drive. 5.9L, 1,000 miles

Aftertreatment as Chemical Reactors

A Predictive Framework - Redox Chemistry



Oxidation of Diesel Exhaust


• Organics (OC, THC, PAHs) ↓

• CO ↓


• NO₂/NO_x ↑

• SO₂ → SO₃ → nucleation ↑

Aftertreatment Significantly Reduces PM and NO_x




PM Mass Reductions of 95%+
(not temperature or cycle dependent)



NO_x Reductions of 75%+
(dependent on temperature, i.e. duty cycle)

Nucleation




- $\text{SO}_2 \rightarrow \text{SO}_3 \rightarrow \text{Nucleation (water or ammonia)}$
- Storage


Accumulation mode seen in:
Veh#1 Baseline

Nucleation mode seen in:

Veh#1 CRT



Veh#1 V-SCRT



Veh#1 Z-SCRT




Veh#2 DPX




No nucleation mode in
Veh#1 Baseline



Veh#3 Horizon



Veh#4 CCRT




Nucleation



Nucleation occurs when a threshold temperature has been reached leading to sulfation

Chemical Composition of PM



- Baseline PM – 50% OC 50% EC
- Nucleating Aftertreatment – Majority Ions such as Sulfate and Ammonium
- Non Nucleating Aftertreatment – Still mostly OC with some EC
 - (DPF preferentially filters EC)

IN VITRO TEST FOR THE TOXICITY OF PARTICULATE MATTER





FIG. 1. Schematic of disease induction pathway from particle exposure.
(Ref: J. G. AYRES ET AL. Inhalation Toxicology, 20:75–99, 2008)


- **Measurement of Oxidative Stress Potential**
 - *in vitro toxicity test*
 - Acellular systems (DTT) / Cellular systems (macrophage cell, DCFH-DA)

OXIDATIVE STRESS POTENTIAL OF TOTAL PM PER PM MASS





- DTT highly correlated with water-soluble organic carbon (WSOC)*
- Uncatalyzed filters better at filtering EC than WSOC
- Catalyzed aftertreatment reduces WSOC

OXIDATIVE STRESS POTENTIAL OF TOTAL PM PER DISTANCE DRIVEN IS REDUCED BY ALL HD RETROFITS



Conclusions

- The decrease of diesel PM and NO_x with the advent of DPFs and SCR will greatly improve air quality in California.
- Secondary effects of diesel aftertreatment are becoming better understood:
 - Oxidation of exhaust is a function of catalytic loading and exhaust temp.
 - As NO_2/NO_x and particle number increase, organics (THC, PAH's, WSOC, etc), CO and DTT expression decrease.
- Not all Ultrafine particles are the same
 - Nucleation mode particles, when present, post aftertreatment are morphologically, chemically and toxicologically different from traditional diesel exhaust particles.



Next Steps

- Effect of toxicity in other assays forthcoming
- Current study based on *passive retrofit* or pre-2010 technology.
- It will be important to test 2010 OEM technology, as effect may be different from what is described here.

Thank you